

Exercise session 09

Optimization, debugging, profiling, testing.

Advanced Programming - SISSA, UniTS, 2024-2025

Pasquale Claudio Africa

25 Nov 2024

Optimization and profiling

Source

Memory layout

Data structure alignment

```
class MyClass
{
    char a;        // 1 byte.
    short int b;  // 2 bytes.
    int c;        // 4 bytes.
    char d;        // 1 byte.
};
```

How data is *not* stored

How data is actually stored

Access patterns and loop tiling (for a row-major matrix)

Examples

The folder `examples/optimization` contains three examples:

1. `data_alignment` compares the memory occupation of two objects containing the same data members but with different data alignment/padding.
2. `loop_unrolling` implements a function that multiplies all elements in a `std::vector` by looping over all its elements and returns the result. The executable compares the performance with those obtained exploiting loop unrolling.
3. `static` implements a function that allocates a `std::vector` and, taking an index as input, returns the corresponding value. The executable compares the performance with those obtained by declaring the vector `static`.

Exercise 1: Optimization

The `hints/ex1/` directory contains the implementation of a class for dense matrices organized as **column-major**.

- Implement `Matrix::transpose()`, a method to compute $A = A^T$.
- Implement `operator*`, a function to compute matrix-matrix multiplication.
- Optimize the matrix-matrix multiplication by transposing the first factor before the computation. Compare the execution speed with the previous implementation.
- Use `valgrind --tool=callgrind` to generate a profiler report.
- Generate a coverage report using `lcov` and `genhtml`.

Debugging

Examples

The content of `examples/debug` was inspired by [this repository](#) and shows basic techniques for debugging as well as an introduction to `gdb`.

Further readings

- [Defensive programming and debugging](#).
- [C++ undefined behaviour 101](#)
- [Shocking undefined behaviour in action](#)

Exercise 2: Debugging

The `hints/ex2/` directory contains an implementation of a double-linked list class. The class stores a pointer to the head, and each node (except for the head and the tail, obviously) contains a pointer to the previous and to the next node.

The implementation contains a lot of errors, namely:

1. Compilation and syntax errors.
2. Runtime errors, including a segmentation fault and a problem in printing the list.
3. Memory leaks.
4. Two possible *segmentation faults*, not captured by the `main`.

With the help of `gdb` and `valgrind`, solve all these issues and make the code working!

Testing

Exercise 3: Testing

The `hints/ex3/` contains a static function to compute the mean of a `std::vector` .

Following the given directory structure and using `Google Test` , fill in the missing parts in `tests/mean.cpp` to check that the function behaves as expected in all the listed cases.

To run the testsuite type

```
make test
```

or

```
ctest
```

from the CMake build folder.